



**DECLARATION OF PERFORMANCE**  
**No ES-501**



**RAVAGO HELLAS S.M.S.A.**

**Ecostir XPS**

<b>1. Unique identification code of the product-type:</b>																							
a) XPS-EN13164-T2-CS(10/Y)200-DS(TH)-WL(T)1,5-MU100-TR200																							
b) XPS-EN13164-T2-CS(10/Y)250-DS(TH)-WL(T)1,5-MU100-TR200																							
c) XPS-EN13164-T2-CS(10/Y)300-DS(TH)-WL(T)1,5-MU100-TR200																							
<b>2. Type:</b>																							
a) Ecostir 10-20mm etics																							
b) Ecostir 30mm etics																							
c) Ecostir 40mm-120mm etics																							
<b>3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification as foreseen by the manufacturer:</b>																							
EN 13164:2012+A1:2015 - Thermal insulation for Buildings (ThIB)																							
<b>4. Name and contact address of the manufacturer:</b>																							
Ravago Hellas S.M.S.A																							
Neratziotissis 101, Marousi, 15124																							
<b>5. System or systems of assessment and verification of constancy of performance of the construction product: AVCP - System 3</b>																							
<b>6. Name and identification number of notified body: GSH (No 0919) and P.C.B.C. (No 1434)</b>																							
<b>7. Declared performance - Essential characteristics EN 13164:2012+A1:2015</b>																							
Dimensional tolerances		EN 823		T										2									
Compressive strength		EN 826		CS(10Y) [kPa]										a)200 b)250 c)300									
Tensile strength		EN 1607		TR [kPa]										200									
Reaction to fire		EN 13501-1		Euroclass										E									
Water permeability		Long term water absorption by total immersion		EN 12087		WL(T) [vol%]						1,5											
		Long term water absorption by diffusion		EN 12088		WD(V) [vol%]						NPD											
Water vapor transmission		Water vapor diffusion resistance factor		EN 12086		MU						100											
Durability of reaction to fire against heat, weathering, ageing/degradation		The reaction to fire performance of XPS does not change with time																					
Thermal resistance and thermal conductivity		see below R <sub>0</sub> and λ <sub>0</sub>																					
Durability of thermal resistance against heat, weathering, ageing/degradation		Dimensional stability under specified temperature and humidity conditions		EN 1604		DS						(70,90) (≤5%)											
<b>Thickness-d<sub>n</sub> [mm]</b>		<b>10</b>		<b>20</b>		<b>30</b>		<b>40</b>		<b>50</b>		<b>60</b>		<b>70</b>		<b>80</b>		<b>100</b>		<b>120</b>			
<b>Thermal resistance-R<sub>0</sub> [(m<sup>2</sup>·K)/W]</b>		EN 12667		0,30		0,60		0,90		1,20		1,50		1,75		2,05		2,35		2,95		3,55	
<b>Thermal conductivity-λ<sub>0</sub> [W/(m·K)]</b>		EN 12667		0,034																			

The performance of the product identified above is in accordance with the performance stated. This statement of performance shall be made in accordance with Regulation (EU) No. 305/2011, with the sole responsibility of the manufacturer identified above.

Name **Apostolos Giannoulis**  
Function **Production Manager**  
Place **Sevasti-Greece**  
Date **01/01/2022**

Signature